

BLUE RIBBON



AUTOMATIC TRANSMISSION FLUID

BLUE RIBBON Automatic Transmission Fluid (ATF) is a traditional ATF formulated with premium base stocks and traditional additive technology. It is designed for use in electronic and hydraulic controlled transmissions and can also be used in other applications such as power steering units, rotary screw compressors, and some hydraulic fluid applications.

FEATURES & BENEFITS:

BLUE RIBBON ATF provides the following benefits:

- Excellent wear protection
- Good anti-foam properties
- Red color for easy identification
- Outstanding oxidation resistance
- A wide range of seal compatibility
- Protection against rust and corrosion
- Superior low-temperature performance providing good cold-start shifting
- Savings from one fluid for virtually all automatic transmission applications
- Superior frictional characteristics with excellent retention and smooth shifting

APPLICATIONS:

BLUE RIBBON ATF is recommended for 1989 through 2006 model General Motors and pre-2007 Ford automatic transmissions, as well as many imports calling for a Dexron-III or Mercon. Additionally, this product is suitable for use in the following applications:

- Where Allison C-4 and Caterpillar TO-2 fluids are required
- In all automatic transmissions built by General Motors (1989-2006) calling for a Dexron-III fluid
- Where Mercon, M2C138-CJ or M2C166-H fluids are required
- Where Dexron-III, Dexron-IIIE, Dexron-II or Type A fluids are required
- In powershift transmissions, torque converters and hydrostatic transmissions
- In some hydraulic and compressor systems where excellent low-temperature fluidity and anti-wear properties are required
- Chrysler recommends Chrysler ATF+3 fluid to be used for complete fluid changes
- In most 1979 or newer transmissions built by Ford (exceptions: Ford FMX, pre-1980 C-4 transmissions, and vehicles requiring Mercon-V)

AVAILABILITY:

BLUE RIBBON ATF is available throughout the Blue Ribbon marketing area. Your Blue Ribbon representative can provide specific information. Need additional information? Call Deckman Oil Co. at 800.836.0562

DECKMAN OIL COMPANY, INC.

9 Norton Street • Honeoye Falls, N.Y. 14472
phone: (585) 624-1630 • (800) 836-0562
fax: (585) 624-2142 • www.deckmanoil.com

BLUE RIBBON AUTOMATIC TRANSMISSION FLUID TYPICAL PROPERTIES

SAE GRADE	5W-20	
	Test Method	
API Gravity, 60°F	ASTM D-1298	32.6
Density, lbs/gal	Calculated	7.19
Viscosity, cSt @ 40°C	ASTM D-445	37.1
Viscosity, cSt @ 100°C	ASTM D-445	7.46
Viscosity, SUS @ 100°F	ASTM D-2161	183
Viscosity, SUS @ 210°F	ASTM D-2161	52
Viscosity Index	ASTM D-2270	190
Brookfield Viscosity, cP @ -40°C	ASTM D-2983	17,500
Brookfield Viscosity, cP @ -20°C	ASTM D-2983	1,300
Pour Point, °F (°C) (max)	ASTM D-97	-38 (-39)
Flash Point, COC, °F (°C)	ASTM D-92	370 (186)
Color	ASTM D-1500	Red

Due to continual product research and development,
the information contained herein is subject to change without notification.