

OIL & GAS LUBRICANTS LINE CARD



AN HF SINCLAIR BRAND

BETTER PERFORMANCE STARTS WITH **SENTRON™**

OUR NO-NONSENSE
LUBRICANTS **WARRANTY**

We will repair equipment or replace equipment parts that are damaged due to defects of a Petro-Canada Lubricants product, as long as the lubricant is used in accordance with your equipment manufacturer's and our recommendations.

IT'S MORE THAN JUST A WARRANTY. **IT'S A COMMITMENT.**

To learn more about how Petro-Canada Lubricants products can help your business, visit **lubricants.petro-canada.com** or contact us at **lubecsr@hfsinclair.com**

Committed to the disciplined operation of our business.



AN HF SINCLAIR BRAND



AN HF SINCLAIR BRAND

LUB4332E (2023.09)
Trademarks are owned or used under license.

**OIL & GAS
LUBRICANTS
LINE CARD**

BETTER PERFORMANCE STARTS WITH **SENTRON™**

COMPRESSOR FLUIDS

PC GasComp™ SP—Water-soluble PAG

PC GasComp™ IP—Water-insoluble PAG

PC GasComp™ HT—Hydrotreated Mineral Based



GEAR OIL

ENDURATEX™ EP—Mineral Based

ENDURATEX™ Synthetic EP—PAO Based

SYNDURO™—PAO Based Multipurpose Oil



TURBINE FLUIDS

TURBOFLO™ R&O—Mineral Based

TURBOFLO™ XL—Premium Mineral Based

TURBOFLO™ LV—Specialty Low Varnishing

TURBOFLO™ HTS—Specialty High Temp & Long Life



Over 30 years of experience allows us to create quality products that give you peace of mind.

STATIONARY GAS ENGINE OILS

SENTRON™ is a line of high-performance, long-life oils used for stationary gas engines and compressors in a wide variety of applications with a key focus on gas compression and power generation. From our ashless to low-ash formulations, these products deliver unparalleled engine performance, reliability and savings.

SENTRON™ LD Synthetic Blend (0.53% wt ash)

A 15W-40 multigrade extension of the SENTRY™ line, formulated as a synthetic blend to extend drain intervals and give better low-temperature performance in comparison to mono-grade SAE 40s.

SENTRON™ LD 8000 (0.52% wt ash)

Provides revolutionary performance for up to 300% longer drain intervals compared to the leading global conventional competitor and helps prevent deposits from ash and worn metal parts. It contains a specialized additive mix that provides greater TBN retention to help neutralize harmful acids.

SENTRON™ LD 3000 (0.47% wt ash)*

Provides a high level of performance in high output turbocharged engines that prefer a low-ash oil.

SENTRON™ LA 2000 (0.50% ash)*

Prevents deposits from excessive ash, resulting in cleaner engines, lower wear on key engine parts and improved engine performance.



HEAVY-DUTY ENGINE OILS

DURON™ HP—High Performance

DURON™ SHP—Synthetic Blend

DURON™ UHP—Full Synthetic

DURON™ GEO—LNG/CNG & API CK-4



NATURAL GAS ENGINE SPECIALTY OILS

SENTRON™ Ashless 40 (0.05% wt ash)

SENTRON™ VLA 40 (0.30% wt ash)

SENTRON™ VTP 0W-30 (0.58% wt ash)

SENTRON™ VTP 10W-40 (0.59% wt ash)



GREASES

PRECISION™—Lithium-based

VULTREX™—Aluminum-based

PEERLESS™—Calcium Sulfonate

PEERLESS™ EMB—Polyurea



*Recommended for most 4-stroke and some 2-stroke stationary gas engines in gas compression applications. Also suitable for use in engines fitted with catalytic converters.



AN HF SINCLAIR BRAND